



Model LS



Model No.	Slider dimensions									
	Max. Stroke ℓ_s	Height M ± 0.25	Width W ± 0.25	Length L	T	L ₁	(K)	B	F	S $\times \ell$
LS 827	13	8	14.2	28.7	7.6	27	0.85	5.5	16	M2 $\times$ 3
LS 852	25	8	14.2	53.7	7.6	52	0.85	5.5	41	M2 $\times$ 3
LS 877	50	8	14.2	78.7	7.6	77	0.85	5.5	66	M2 $\times$ 3
LS 1027	13	10	19	28.7	9.2	27	0.85	8.5	16	M3 $\times$ 3.5
LS 1052	25	10	19	53.7	9.2	52	0.85	8.5	41	M3 $\times$ 3.5
LS 1077	50	10	19	78.7	9.2	77	0.85	8.5	66	M3 $\times$ 3.5



Unit: mm

	Base dimensions					Static permissible moment ¹		Basic load rating		Mass
	Width	Height	$d_1 \times d_2 \times h$	Length	f_1	M_A, M_B	M_C	C	C_0	
	W_1	H		L_0		N·m	N·m	N	N	
	6.2	4.7	$2.2 \times 3.9 \times 1.4$	27	19	0.2	0.29	39.2	68.6	9
	6.2	4.7	$2.2 \times 3.9 \times 1.4$	52	35	0.49	0.39	68.6	118	15
	6.2	4.7	$2.2 \times 3.9 \times 1.4$	77	60	0.88	0.59	98	167	21
	9.6	6.2	$3.3 \times 6 \times 3.1$	27	19	0.29	0.59	58.8	108	13
	9.6	6.2	$3.3 \times 6 \times 3.1$	52	35	0.78	1.08	108	186	23
	9.6	6.2	$3.3 \times 6 \times 3.1$	77	60	1.47	1.57	157	275	34

¹ M_A , M_B and M_C each indicate the permissible moment per LM system, as shown in the figure above.