


Easy-mount Cam Follower Model CF-SFU

Optional specifications		Symbol
Roller guide	With cage	No Symbol
Material	Carbon steel	No Symbol
Seal	With seal	No Symbol
Outer ring shape	Cylindrical outer ring	No Symbol
	Spherical outer ring	R



Stud diameter		Main dimensions										
		Outer diameter	Outer ring width		Overall length							
d	Model No.	D	C	B	B ₁	B ₂	C ₁	l ₁	l ₂	d ₁	r _{min}	e
6	CF-SFU-6	16	11	12	32	20	0.6	5	10	4	0.3	0.3
8	CF-SFU-8	19	11	12	32	20	0.6	5	10	4	0.3	0.5
10	CF-SFU-10	22	12	13	33	20	0.6	5	10	4	0.3	0.5
10	CF-SFU-10-1	26	12	13	33	20	0.6	5	10	4	0.3	0.5
12	CF-SFU-12	30	14	15	35	20	0.6	5	10	6	0.6	1
12	CF-SFU-12-1	32	14	15	35	20	0.6	5	10	6	0.6	1
16	CF-SFU-16	35	18	19.5	44.5	25	0.8	10	10	6	0.6	1
18	CF-SFU-18	40	20	21.5	46.5	25	0.8	10	10	6	1	1
20	CF-SFU-20	52	24	25.5	50.5	25	0.8	10	10	8	1	1
20	CF-SFU-20-1	47	24	25.5	50.5	25	0.8	10	10	8	1	1

Note: For information on accuracy standards, please refer to **A19-14**.

Model number coding

CF-SFU-6 R -N

Model No.


No Symbol : Cylindrical outer ring
R : Spherical outer ring

No Symbol : No grease nipple

N : Dedicated grease nipple included (See **A19-39**)

Notes: Model CF-SFU is fitted with UU seals even where no UU symbol is used.

For accessories, please refer to **A19-38**.



Model CF-SFU···R

Unit:mm

	Mounting dimensions				Basic load rating		Maximum permissible load	Track load capacity		Rotational speed limit¹	Mass
	Mounting dimension H		Shoulder height	Withcage		F₀		Cylindrical outer ring	Spherical outer ring	Withcage	With cage
	Tolerance	t	f	h	C						
	H7	(Min.)	(Min.)	(reference value)	kN	kN	kN			min⁻¹	g
	6	20	11	10	3.59	3.58	2.11	3.43	1.08	17500	19
	8	20		1310	4.17	4.65	4.73		4.021.37	14000	28.5
	10	20		1510	5.33	6.78	5.81		4.71.67	11900	43
	10	20		1510	5.33	6.78	5.81		5.492.06	11900	58.5
	12	20		2010	7.87	9.79	9.37		7.062.45	9800	93
	12	20		2010	7.87	9.79	9.37		7.452.74	9800	103
	16	25		2415	12	18.3	17.3		11.23.14	7000	163.5
	18	25		2615	14.7	25.2	26.1		14.43.72	5950	235
	20	25		3615	20.7	34.8	32.1		23.28.23	4900	436
	20	25		3615	20.7	34.8	32.1		217.15	4900	361

¹ The rotational speed limit applies to models with grease lubrication and seals.

Note: Model CF-SFU is delivered with a stopper plug fitted.